

**Specifications**

Operating Voltage		36 – 70 VDC
Operating Power		65 W Peak
Operating Current		1.8 A Peak
Depth Rating	Standard	60 m (200 ft)
	Deep Water	300 m (1,000 ft)
Speed	Pan	0 – 26 °/s
	Tilt	0 – 9 °/s
Range	Pan	360 ° Continuous
	Tilt	260 ° (+/- 130 °)
Dimensions	Standard	Ø90 x 273 mm (Ø3.5 x 10.8 in)
	Deep Water	Ø90 x 298 mm (Ø3.5 x 11.7 in)
Weight	Aluminum	2.8 kg (6.1 lb)
	Stainless Steel	5.5 kg (12.2 lb)
Imager	Sensor	1/2.8in Exmor R CMOS (NTSC or PAL)
	Lens	f = 5.1 to 51 mm
		120x Zoom (10x Optical, 12x Digital)
	Focus	Manual or Auto
	Horizontal Resolution	720 TVL
	Minimum Illumination	0.5 lux
	HFOV	54 ° (air)
Depth of Field	10 mm (0.4 in) to infinity	
Lights		3 x High intensity LEDs
Lasers (optional)		2 x Laser Lines, 635 nm, 30 mm (1.18 in) Spacing
Controls		Pan, tilt, zoom, focus, lights, lasers, exposure
Maximum Tether Length		500 m (1,650 ft)
Operating Temperature		0 – 50 °C (32 – 122 °F)
Storage Temperature		-20° – 60 °C (-4 – 140 °F)